



DATA SHEET

TEAK RENOVATOR NETATECK

The **NETATECK RENOVATOR** is used for cleaning the teak decks of pleasure boats. It is used not only to clean and whiten wood, but also to revive the colour of wood which had deteriorated under the effects of the weather. It also removes mosses. It is used pure or diluted with water, depending on the state of the surface to be cleaned. It is safe on plastics and paints. If traces of the old covering needs to be removed (paint, varnish, etc...), use an appropriate stripping product before the use of **NETATECK**.

BIODEGRADABLE 83 % AT 28 DAYS according to OECD test 301D

PHYSICAL CHARACTERISTICS

Appearance : Colourless to slightly yellowish liquid.
Density at 20°C : 1.05 g/cm³
pH pure : 1
Solubility : Total in water
Flash point: > 60°C

APPLICATION

NETATECK dilutes very easily in water with a little stirring.
Dilution varies from 3 to 20% according to the cleaning difficulty. It can also be used as a bath, sprayed, etc.
Dampen the wood with fresh water, apply **NETATECK** with a brush, rub lightly, the product foams a little. Leave it to act for 10 to 15 minutes and then rinse with a water jet.
repeat this operation if necessary.
Leave to dry thoroughly before the application of **OILTECK** teak oil.

PACKING AND STORAGE

Packaging : 500 ml and 1 L
Storage: One year in a closed container at temperature between 0 and 50°C. Dislikes the frost.

PRECAUTIONS FOR USE

Wearing gloves and goggles is recommended for handling. Keep out of reach of children.

HEALTH AND SAFETY

See data sheet

*This information corresponds to the actual state of our knowledge and has the sole object of informing you about our products and possible applications. It is objectively given but does not imply any guarantee by us.
Our company may modify all these details at any time*